

Data Systems

Initial AHATS data system configuration. Note: this was changed later, see [changed serial cards at upwind, downwind2](#)

name	viper #	box	IP	tower	net link	serial #0	serial #1
profile	3	6	192.168.14.103	profile	eanth	8P W274095	8M 240017
downwind1	6	14	192.168.14.106	d4	hub in profile	8M W249918	8M 250043
downwind2	1	13	192.168.14.101	d10	eanth	8P W274177	8M W249924
upwind	2	1	192.168.14.102	u7	hub in downwind2	8P W274198	8M W240025
pressure1	10	small	192.168.14.110	d4	hub in profile		
pressure2	11	large	192.168.14.111	d10	hub in downwind2		

To prevent the AP24 from serving addresses to the vipers, I entered these commands:

```
ip dhcp-server lease
add mac-address 00:80:66:10:43:96 block-access=yes
add mac-address 00:80:66:10:43:8C block-access=yes
add mac-address 00:80:66:10:43:92 block-access=yes
add mac-address 00:80:66:10:43:8D block-access=yes
add mac-address 00:80:66:10:43:C5 block-access=yes
add mac-address 00:80:66:10:42:A6 block-access=yes
add mac-address 00:80:66:10:43:96 block-access=yes
```